



**SFC 709 Ex** 



## Specifications

	TATA 497 TC, water-cooled direct injection diesel
Engine type	engine with inter-cooler
Engine capacity (cc)	3783
Max engine output	66.2 kW (90 Ps) at 2400 rpm
Max engine torque	325 Nm (33.14 Kgm) at 1300 - 1600 rpm
Emission norms	Euro II
TRANSMISSION AND STEE	RING
Clutch	Single plate dry friction type
Gearbox	GBS-27 syncromesh, 5 forward 1 reverse
Steering	Power steering
SUSPENSION	
Front	Semi elliptical leaf spring
Rear	Semi elliptical leaf spring with auxiliary springs
Shock absorber	Hydraulic double acting telescopic type at front and r
FRAME	
Туре	Ladder type frame with rivetted / bolted cross members, side members are of channel section, dep 200 mm (max), flange width: 60 mm, thickness: 5 mm
BRAKE	
Service brake	Dual circuit full air S-CAM brake
WHEELS AND TYRES	
No.	6+1
Size	7.5 R16-14PR
DIMENSIONS	
Wheel base (mm)	3800
AN / NO 1 ME 1 ME	

	Overall length (mm)	6029
	Max width (mm)	2132
1	WEIGHTS	
	Kerb weight (Kg)	2715
	GVW (Kg)	7500
(	PERFORMANCE	
	Grade ability	27%
	Top speed (kmph)	90
	Minimum turning circle diameter in mm	13.5

## For more information, please contact:

## **TATA MOTORS**

International Business, One Indiabulls, Tower 2A, 14<sup>th</sup> Floor 841, S.B Marg, Elphinstone Road, Mumbai 400 013