




Prima 4938.S



Specifications

ENGINE ENGINE	
Engine type	Cummins ISLe 8.9L Euro 3, turbo intercooled
Engine capacity (cc)	8900
No. of cylinders	6 cylinders inline
Max engine output	380 Hp @ 2100 rpm 1550 Nm @ 1200 - 1400 rpm
Max engine torque	
Fuel type	Diesel
TRANSMISSION AND STEERING	
Clutch	430 mm
Gearbox	EATON FSO 10309 - OD
Туре	Manual
No. of gears	9 Speed with 1 crawler and 1 reverse
Gear ratios (1st)	10.04
Steering	Power steering, telescopic and tiltable
Drive type	4x2
SUSPENSION	
Front	Parabolic leaf spring
Rear	Semi elliptical leaf spring
BRAKES	
Service brake	Full air dual circuit with EBC
Parking brakes	Spring actuated on rear axle
Engine brake	Jake brake

	Tyre size	315 / 80 R 22.5 18PR (Front & Rear), Radial
	Wheel rim	9 x 22.5 steel rim
	Front axle	Heavy duty forged I beam Reverse Elliot typ
	Rear axle	TATA RA - 210
	Drive axle type	Planetary hub reduction
	5th wheel coupling size	2 inch fabricated coupling (JOST)
	Spare wheel carrier	Yes
9	DIMENSIONS	
	Wheelbase (mm)	3890
	TCD (mm)	14220
	Overall length (mm)	7008
	Max. width (wt. body)	2585
	Overall height (wt. body)	3320
	Front overhang (mm)	1720
	Rear overhang (mm)	800
4	Tank capacity (ltrs)	625
	WEIGHTS	
	Max. GCW (Kgs)	49000
	Max. FAW (Kgs)	6000
	Max. Raw (Kgs)	19000
	Max GVW (Kgs)	9970
	Total unladen weight (Kgs)	9970



For more information, please contact:

TATA MOTORS

International Business, One Indiabulls, Tower 2A, 14th Floor 841, S.B Marg, Elphinstone Road, Mumbai 400 013