



LPT 407 Ex TT



Specifications

Engine type	TATA 4SP turbo intercooler, water-cooled direct injection diesel engine
Engine capacity (cc)	2956
Max engine output	75 kW (100 Ps) at 2800 rpm
Max engine torque	300 Nm at 1400 - 1500 rpm
Emission norms	BS III
TRANSMISSION AND STEE	RING
Clutch	Single plate dry friction type
Gearbox	GBS-27, 5 forward 1 reverse
Steering	Power steering
SUSPENSION	
-ront	Semi elliptical leaf spring
Rear	Semi elliptical leaf spring
Shock absorber	Hydraulic double acting telescopic type at front and rear
FRAME	
Гуре	Ladder type frame with rivetted / bolted cross members, side members are of 'C' channel section, depth: 200 mm (max), width: 60 mm and thickness: 5 mi
BRAKE	
Service brake	Vacuum assisted dual circuit hydraulic with tandem master cylinder
WHEELS AND TYRES	
No.	6+1
Size	6.50 x 16 -10 PR
Wheel base (mm)	2775
101 1 mg 1 mg	

	Overall length (mm)	5000
	Max width (mm)	2140
1	WEIGHTS	
	Kerb weight (Kg)	2550
	GVW (Kg)	4550
(PERFORMANCE	
	Grade ability	31%
	Top speed (kmph)	99
	Minimum turning circle diameter in mm	10.2

For more information, please contact:

TATA MOTORS

International Business, One Indiabulls, Tower 2A, 14th Floor 841, S.B Marg, Elphinstone Road, Mumbai 400 013