



LPT 809 Ex2



Specifications

Engine type	TATA 497 TCIC, water cooled direct injection diesel engine with inter-cooler
Engine capacity (cc)	3783
Max engine output	66.3 kW (90 Ps) at 2400 rpm
Max engine torque	325 Nm at 1300 - 1600 rpm
Emission norms	Euro II
TRANSMISSION AND STEERIN	NG
Clutch	Single plate dry friction type
Gearbox	GBS-27 synchromesh, 5 forward 1 reverse
Steering	Power steering
SUSPENSION	
Front	Semi elliptical leaf spring
Rear	Semi elliptical leaf spring with auxiliary springs
Shock absorber	Hydraulic double acting telescopic type at front and
FRAME	
Туре	Ladder type frame with rivetted / bolted cross members, side members are of channel section, depth: 200 mm (max), width: 60 mm
BRAKE	
Service brake	Dual circuit full air S-CAM brake
WHEELS AND TYRES	
No.	6+1
Size	7.50 x 16 - 16 PR
DIMENSIONS	
Wheel base (mm)	3400, 3800

	Overall length (mm)	6225, 6875
	Max width (mm)	2155
1	WEIGHTS	
	Kerb weight (Kg)	2732 & 3312 (CLB), 2792 & 3402 (CLB)
	GVW (Kg)	8720
	PERFORMANCE	
	Grade ability	25%
	Top speed	85
	Minimum turning circle diameter in mm	12.3, 13.5

For more information, please contact:

TATA MOTORS

International Business, One Indiabulls, Tower 2A, 14th Floor 841, S.B Marg, Elphinstone Road, Mumbai 400 013