



**LPK 909 Ex** 



## Specifications

Engine type	Tata 497 TCIC, water-cooled direct injection diesel
Ligine type	engine with intercooler
Engine capacity (cc)	3783
Max engine output	66.3 kW (90 Ps) at 2400 rpm
Max engine torque	325 Nm at 1300 - 1600 rpm
Emission norms	BS II
TRANSMISSION AND STEERING	
Clutch	Single plate dry friction type
Gearbox	GBS 40, 5 forward 1 reverse
Steering	Power steering
SUSPENSION	
Front	Semi elliptical leaf spring
Туре	Semi elliptical leaf spring with auxiliary springs
Shock absorber	Hydraulic double acting telescopic type at front and re
FRAME	
Туре	Ladder type heavy duty frame with rivetted / bolted cross members, side members are of channel section depth: 200 mm (max), width: 60 mm
BRAKE	
Service brake	Dual circuit full air S-CAM brake
WHEELS AND TYRES	
No.	6+1
Size	F - 8.25 x 16 -16 PR Rib type; R - Lug type
DIMENSIONS	
Wheel base (mm)	2775
** / ME   ME   ME	

Overall lengtl	n (mm)	5000
Max width (mm)		2155
WEIGH	тѕ	
Kerb weight	(Kg)	4075 (light weight), 2850 (cab chassis)
GVW (Kg)		9600
PERFO	RMANCE	
Grade ability		26%
Top speed (k	mph)	85
Minimum tur	ning circle diameter in mm	10.2

## For more information, please contact:

## **TATA MOTORS**

International Business, One Indiabulls, Tower 2A, 14<sup>th</sup> Floor 841, S.B Marg, Elphinstone Road, Mumbai 400 013