



Prima LX 2528.K

## Specifications

\* / BR / BR | BR | BR

ngina tuna	Cumming ICDs 6.7 DC III /Dash LID saggesting
ngine type	Cummins ISBe 6.7 BS III (Bosh HP common rail)
ngine capacity (cc)	6700
lax engine output	266 BHP at 2500 rpm
Bore / stroke	107 mm x 124 mm
Max engine torque	975 Nm at 1500 rpm
TRANSMISSION AND STEE	RING
Clutch	430 mm, organic
Gearbox	Tata G1150 DD, 8 forward + 1 reverse
Crawler	12.868
st	9.139
nd	6.725
rd	4.903
th	3.571
th	2.559
th	1.883
th	1.373
th	
everse	13.4
FRAME	
ype	Ladder type heavy duty frame of channel section
Chassis	286 mm x 90 mm x 7 mm
rame width	Front - 950, Rear - 850

Front	Develorie 7.5T
Front	Parabolic - 7.5T
Rear	Bogie - 37T
BRAKES	
Service brake	Dual circuit full air S-CAM brake
Brake area	410 x 220
Engine exhaust brake	Pneumatically operated with foot control valve au slack adjuster
WHEELS AND TYRES	
Tyre size	11 x 20 18PR
Wheel rim	8.00 x 20
Rear axle	RA 210 - Two Stage Reduction
Final drive ratio	7.246
Rear axle weight	Front - 16T, Rear - 16T
Front axle	I Beam - 7.5T
DIMENSIONS	
Wheel base	3950
TCD	16770
Front track	2074
Rear track	1907
Ground clearance	Front - 289, Rear - 253
Max. width (wt. body)	2590
Overall height (wt. body)	3568
Box body options (CBM)	16
Scoop body option (CBM)	14

WEIGHTS	
Max. GCW	25000
Max. FAW	6000
Max. Raw	19000
Tare weight	12700 (FB)
PERFORMANCE	
Grade ability	33% / 52%
Top speed (kmph)	89
CABIN	
Cabin type	4 point suspended Prima Lx Day Cabin
AC	Optional

## For more information, please contact:

## **TATA MOTORS**

International Business, One Indiabulls, Tower 2A, 14<sup>th</sup> Floor 841, S.B Marg, Elphinstone Road, Mumbai 400 013