



LPT 407 Ex ST



Specifications

Engine type	Tata 497 SP turbo, water-cooled direct injection diesel engine
Engine capacity (cc)	2956
Max engine output	100 Ps at 2800 rpm
Max engine torque	300 Nm at 1400 - 1500 rpm
Emission norms	BS III
TRANSMISSION AND STEERII	NG
Clutch	Single plate dry friction type
Gearbox	GBS-27, 5F + 1R
Steering	Manual
SUSPENSION	
Front	Semi elliptical leaf spring
Rear	Semi elliptical leaf spring
Shock absorber	Hydraulic double acting telescopic type at front and rear
FRAME	
Туре	Ladder type frame with rivetted / bolted cross members, side members are of 'C' channel section, depth: 200 mm (max) width: 60 mm and 5 mm thick
BRAKE	
Service brake	Vacuum assisted dual circuit hydraulic with tandem master cylinder
WHEELS AND TYRES	
No.	4+1
Size	8.25 x 16 -16 PR rib type (front) 8.25 x 16 -16 PR lug type (rear)

DIMENSIONS	
Wheel base (mm)	3400
Overall length (mm)	5909
Max width (mm)	2140
WEIGHTS	
Kerb weight (Kg)	2420
GVW (Kg)	6250
PERFORMANCE	
Grade ability	31%
Top speed (kmph)	100
Minimum turning circle diameter in mm	12.3

For more information, please contact:

TATA MOTORS
International Business, One Indiabulls, Tower 2A, 14th Floor 841, S.B Marg, Elphinstone Road, Mumbai 400 013